



## Generator Set Technical Specification Sheet

**Model: GSW 200**

**General Features:**

	3 Phase	
Emergency standby power	<b>220.0</b>	kVA
	<b>176.0</b>	kW
Continuous power	<b>208.0</b>	kVA
	<b>167.0</b>	kW
Power factor	<b>0.8</b>	Cosfi
Nominal voltage	<b>400 Y</b>	Volt
Nominal frequency	<b>50</b>	Hz
Alternator connections	<b>Star</b>	
Continuous power : At variable load according to ISO 3046 (ICN2)		

**Engine:**

Brand / Model		<b>Volvo / TAD 722 GE</b>
Type / Stroke		<b>Diesel / 4 stroke / Direct Injection</b>
Number of cylinders / Configuration		<b>6 / in-line</b>
Cubic capacity	ltr	<b>7.15</b>
Aspiration		<b>Turbo charged with water to air intercooled</b>
Cooling system		<b>Water cooled</b>
Starting system / voltage		<b>Electric / 24</b>
RPM	rpm	<b>1500</b>
Horsepower Prime	kW	<b>179</b>
Oil capacity	litres	<b>34</b>
Coolant Capacity	litres	<b>42</b>
Fuel consumption @ 75% load	Litres/h	<b>32.44</b>
Governor		<b>Electronic to G3</b>

**Alternator:**

Brand / Model		<b>Stamford UCI 274H</b>
Number of poles / rpm		<b>4 pole / 1500 rpm</b>
Voltage / Frequency	Volts / Hz	<b>400 Y / 50</b>
Nominal power	kVA	<b>212.0</b>
Power factor	Cosfi	<b>0.8</b>
Active power	kW	<b>170.0</b>
Efficiency @ 75% load	%	<b>93.3</b>
Maximum overload		<b>10% for 1 hour in every 6 hours of operation</b>
Voltage regulator		<b>Electronic (± 1.5% with 4% engine governing)</b>

**General Installation Data**

Combustion air flow	m <sup>3</sup> /min	
Cooling air airflow	m <sup>3</sup> /min	<b>132</b>
Exhaust gas flow	m <sup>3</sup> /min	
Exhaust gas temperature	°C	
Exhaust system back pressure	mbar	

**Overall Dimensions & Weight:**

		<b>Open Set</b>	<b>Canopy Set</b>
Length	mm	<b>2650</b>	<b>3500</b>
Width	mm	<b>1100</b>	<b>1300</b>
Height	mm	<b>1850</b>	<b>2150</b>
Weight	kg	<b>2030</b>	<b>2775</b>
Fuel tank capacity	Litres	<b>410</b>	<b>330</b>
Run time @ 75% of rated load	h	<b>12.6</b>	<b>10.2</b>
Noise Level @ 7 mtrs	dB(A)	<b>74</b>	<b>74</b>

The specifications quoted above are a guide only and in line with our policy of continuous product development, we reserve the right to vary the specifications at any time without notice.