



Generator Set Technical Specification Sheet

Model: Tramontana 1710

General Features:

	3 Phase	
Emergency standby power	1880	kVA
	1504	kW
Continuous power	1709	kVA
	1367	kW
Power factor	0.8	Cosφ
Nominal voltage	400 Y	Volt
Nominal frequency	50	Hz
Alternator connections	Star	
Prime power according to ISO 3046 (ICN2) at variable load measured at 300 m a s l & 25°C ambient temperature		

Engine:

Brand / Model		Perkins / 4016TWG2
Type / Stroke		Diesel / 4 stroke / Direct Injection
Number of cylinders / Configuration		16 / V
Cubic capacity	ltr	61.123
Aspiration		Turbocharged and air to air charge cooled
Cooling system		Water cooled
Starting system / voltage		Electric / 24v
RPM	rpm	1500
Horsepower Prime	kW	1550
Oil capacity	litres	237.2
Coolant Capacity	litres	295
Fuel consumption 75% load	Litres/h	353
Governor		

Alternator:

Brand / Model		Mecc Alte or Stamford
Number of poles / rpm		4 pole / 1500 rpm
Voltage / Frequency	Volts / Hz	400 Y / 50
Nominal power	kVA	
Power factor	Cosφ	0.8
Active power	kW	
Efficiency @ 75% load	%	
Maximum overload		
Voltage regulator		

General Installation Data:

Combustion air flow	m ³ /min	
Cooling air airflow	m ³ /min	
Exhaust gas flow	m ³ /min	
Exhaust gas temperature	°C	
Exhaust system back pressure	mBar	

Overall Dimensions & Weight:

		Open Set	Canopy Set
Length	mm	5550	8050
Width	mm	2300	2450
Height	mm	2800	4150
Weight	kg		
Fuel tank capacity	Litres		
Run time @ 75% of rated load	h		
Noise Level @ 7 mtrs	dB(A)		75

The specifications quoted above are a guide only and in line with our policy of continuous product development, we reserve the right to vary the specifications at any time without notice.