



Generator Set Technical Specification Sheet

Model: Tramontana 930

General Features:

	3 Phase	
Emergency standby power	1023	kVA
	819	kW
Continuous power	930	kVA
	744	kW
Power factor	0.8	Cosφ
Nominal voltage	400 Y	Volt
Nominal frequency	50	Hz
Alternator connections	Star	
Prime power according to ISO 3046 (ICN2) at variable load measured at 300 m a s l & 25°C ambient temperature		

Engine:

Brand / Model		Perkins / 4008TAG2A
Type / Stroke		Diesel / 4 stroke / Direct Injection
Number of cylinders / Configuration		8 / In Line
Cubic capacity	ltr	30.561
Aspiration		Turbocharged and air to air charge cooled
Cooling system		Water cooled
Starting system / voltage		Electric / 24v
RPM	rpm	1500
Horsepower Prime	kW	947
Oil capacity	litres	165
Coolant Capacity	litres	162
Fuel consumption 75% load	Litres/h	223
Governor		

Alternator:

Brand / Model		Mecc Alte or Stamford
Number of poles / rpm		4 pole / 1500 rpm
Voltage / Frequency	Volts / Hz	400 Y / 50
Nominal power	kVA	
Power factor	Cosφ	0.8
Active power	kW	
Efficiency @ 75% load	%	
Maximum overload		
Voltage regulator		

General Installation Data:

Combustion air flow	m ³ /min	
Cooling air airflow	m ³ /min	
Exhaust gas flow	m ³ /min	
Exhaust gas temperature	°C	
Exhaust system back pressure	mBar	

Overall Dimensions & Weight:

	Open Set	Canopy Set
Length	mm 4700	7050
Width	mm 1900	2000
Height	mm 2400	3800
Weight	kg	
Fuel tank capacity	Litres	
Run time @ 75% of rated load	h	
Noise Level @ 7 mtrs	dB(A)	75

The specifications quoted above are a guide only and in line with our policy of continuous product development, we reserve the right to vary the specifications at any time without notice.